

# ODIN LT SERIES

## COMPACT THERMAL MONOCULARS



- ATN OBSIDIAN LT CORE
- USB C PORT IN OPTIONAL RECHARGEABLE BATTERY
- STEP ZOOM
- ERGONOMIC DESIGN
- LIGHT WEIGHT

### DESCRIPTION

The ATN ODIN LT has been completely redesigned from top to bottom. This thermal handheld scanner is lighter and ergonomically designed to be hand held or mounted to a helmet or headgear for observation. Slim and ergonomic, fits perfectly in your hand. Using our new Obsidian LT Core and Cutting-Edge sensors for sharp crisp images and extended range. Now you can use single use CR123A batteries or the optional rechargeable battery in this device.

This is one tool you'll want with you at all times. Recovery efforts will seem effortless, finding game will no longer be frustrating or hard to find. Search and Rescue operations will be quicker and more efficient!



### SPECIFICATIONS

|                                   | ODIN LT 160<br>4-8x  | ODIN LT 160<br>6-12x | ODIN LT 160<br>8-16x             | ODIN LT 320<br>2-4x    | ODIN LT 320<br>3-6x              | ODIN LT 320<br>4-8 x |
|-----------------------------------|--|----------------------|----------------------------------|------------------------|----------------------------------|----------------------|
| <b>SKU</b>                        |  |                      |                                  |                        |                                  |                      |
| <b>Objective lens</b>             | 19 mm  | 25 mm                | 35 mm                            | 19 mm                  | 25 mm                            | 35 mm                |
| <b>Resolution</b>                 | 160x120, 60 fps, 12 µm   |                      |                                  | 320x240, 60 fps, 12 µm |                                  |                      |
| <b>Magnification</b>              | 4-8x   | 6-12x                | 8-16x                            | 2-4x                   | 3-6x                             | 4-8x                 |
| <b>Field of view</b>              | 5.8°x4.4°  | 4.4°x3.3°            | 3.2°x2.5°                        | 11.6°x8.7°             | 8.8°x6.6°                        | 6.3°x4.7°            |
| <b>Core</b>                       | ATN Obsidian Core LT   |                      |                                  |                        |                                  |                      |
| <b>Display Resolution</b>         | 1280x960 px  |                      |                                  |                        |                                  |                      |
| <b>Eye relief</b>                 | 25 mm  |                      |                                  |                        |                                  |                      |
| <b>Color modes</b>                | White Hot / Black Hot  |                      |                                  |                        |                                  |                      |
| <b>Battery type</b>               | 1 x CR123A (Li-ion)  |                      |                                  |                        |                                  |                      |
| <b>Battery life (Li-ion)</b>      | 2.5 Hrs (or Optional Rechargeable Battery with 5 Hrs of runtime) |                      |                                  |                        |                                  |                      |
| <b>Charging</b>                   | USB, type C port is on the Optional Rechargeable Battery         |                      |                                  |                        |                                  |                      |
| <b>IP rating</b>                  | Weather resistant  |                      |                                  |                        |                                  |                      |
| <b>Human Detection Range</b>      | 475 m  | 625 m                | 940 m                            | 535 m                  | 910 m                            | 1510 m               |
| <b>Human Recognition Range</b>    | 240 m  | 315 m                | 430 m                            | 380 m                  | 455 m                            | 680 m                |
| <b>Human Identification Range</b> | 160 m  | 210 m                | 280 m                            | 230 m                  | 290 m                            | 340 m                |
| <b>Operating Temperature</b>      | -20°F to +120°F / -28°C to 48°C                                  |                      |                                  |                        |                                  |                      |
| <b>Dimensions</b>                 | 5.16"x2.8"x1.81"<br>131x71x46 mm                                 |                      | 5.71"x2.8"x2.01"<br>145x71x51 mm |                        | 5.16"x2.8"x1.81"<br>131x71x46 mm |                      |
| <b>Weight</b>                     | 285 g  |                      | 342 g                            |                        | 285 g                            |                      |
| <b>Warranty</b>                   | 3 years  |                      |                                  |                        |                                  |                      |

\*Specifications subject to change without notice